



# Cradle Stability testing

MDF spacers, 2 Linear Bearings




	Radians	Degrees
Mean Y	1.12E-05	0.0006391161378
Max Y	1.58E-01	9.078544912

Split rings, 4 linear bearings




	Radians	Degrees
Mean Y	8.45E-05	0.004841776066
Max Y	1.62E-01	9.293165734

MDF spacer on 2 Linear Bearings, Split rings on 2 Linear Bearings



	Radians	Degrees
Mean Y	-5.80E-05	-0.003323452525
Max Y	1.46E-01	8.383934999

Washers, 4 Linear Bearings




	Radians	Degrees
Mean Y	8.53E-05	0.004885246374
Max Y	7.93E-02	4.541670284

## Cradle Stability testing


### Test parameters

---

Measurement device : **Samsung Galaxy S8 mini**  
Units : **Radians**



### Phone orientation



### Operating details

10 seconds delay  
5 seconds up  
5 seconds down

Driven by **Bosch Hand Drill** directly to shaft  
*Drill settings* : 1 , drill state , 1

### Findings

---

The lowest average was with 2 MDF spacers at **0.0006 Degrees**

The lowest average with 4 total linear bearings, 2 MDF spacers , 2 Split rings at **0.003 Degrees**

Using 4 linear bearings with just flat washers the smallest maximum angular deviation **4.54 Degrees**

All test units reached equilibrium (**approximately 0 degrees**) at the end of the test

This indicated that the final resting point of the cradle is even and the wobble in transit doesn't effect the final position of the cradle